

**Compressor Oil H2000**  
**2000 Hour Rotary Vans Compressor Lubricant**  
Product Code: ABC

**Product Description**

Cages Compressor Oil H2000 is formulated from carefully selected, highly refined mineral base oils and incorporates additives to give improved anti-wear, anti-oxidation, anti-corrosion and anti-foaming properties. This product exhibits high oxidation stability and good anti wear properties coupled with the low carbon forming tendencies required by rotary vane compressors.

**Applications**

Compressor Oil H2000 has been developed to meet the requirements of rotary vane compressors such as Hydrovane type compressors. This product is designed for the service intervals up to 2000 hours in normal operating conditions, in more severe operating conditions more frequent oil changes will be required.

**Typical Test Data**

Compressor Oil	ABC H2000
ISP/SEA Viscosity	150
Density @ 15°C	0.89
K.V. @ 40°C cSt	150
K.V. @ 100°C cSt	14.9
Viscosity Index	100
Flash Point °C	255

**Availability**

Cages Compressor Oil H2000- is available in bulk, 1000 litre IBC's, 205 barrels, 25 litre drums, 5 litre and 1 litre plastic bottles.

**Storage**

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

**Health and Safety**

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Cages Ltd is one of continual improvement; we therefore reserve the right to change specifications without notice.