

Compressor Oil H4000 D46
High Quality 4000 Hour Compressor Lubricant
Product Code: ABF

Product Description

Cages Compressor Oil H4000 D46 is formulated from carefully selected, highly refined mineral base oils and incorporates additives to give improved anti-wear, anti-oxidation, anti-corrosion and anti-foaming properties. This product exhibits high oxidation stability coupled with the low carbon forming tendencies by many compressors. It also has the additional benefit of the improved detergency which helps maintain excellent internal surface cleanliness.

Applications

Compressor Oil H4000 D46 is recommended for the lubrication of a wide range of compressors including rotary / screw, and many rotary vane type compressors. This oil is designed to give safe, effective and reliable lubrication through the service life of the compressor up to 4000 hours. The combination of oxidation stability and detergency reduces deposit formation even in machines working under severe environmental conditions helping to maintain the performance of the compressor.

Typical Test Data

Compressor Oil	ABF D46
ISP/SEA Viscosity	46
Density @ 15°C	0.87
K.V. @ 40°C cSt	46
K.V. @ 100°C cSt	6.8
Viscosity Index	100
Flash Point °C	205

Availability

Cages Compressor Oil H4000 D46 is available in bulk, 1000 litre IBC's, 205 barrels, 25 litre drums, 5 litre and 1 litre plastic bottles.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health and Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Cages Ltd is one of continual improvement; we therefore reserve the right to change specifications without notice.