

Ultracomp H2000 Range

High Quality 2000 Hour Compressor Lubricants

Product Code: AB0, Ab1, AB2, AB3, AB4, AB5, AB6, AB9

Product Description

Cages Ultracomp H2000 compressor oils are formulated from carefully selected, highly refined virgin mineral base oils and incorporate an ashless additive system to give improved anti-wear, anti-oxidisation, anti-corrosion and anti-foaming properties. These products exhibit high oxidation stability coupled with the low carbon forming tendencies required by many compressors and are recommended for drain intervals of up to 2000 hours in normal operating conditions.

Applications

The Ultracomp H2000 range is recommended for the lubrication of a wide range of compressors including rotary / screw, reciprocating, and many rotary vane type compressors. The oils in this range are designed to give safe, effective and reliable lubrication through the service life of the compressor. These oils are suitable for use where a DIN 51506 category VD-L type oil is required.

Typical Test Data

Ultracomp H2000	AB0	AB1	AB2	AB3	AB4
	S32	S46	P68	P100	V150
ISO / SAE Viscosity	32	46	68	100	150
Density @ 15oC	0.88	0.87	0.88	0.88	0.89
K.V @ 40°C cSt	31.4	6.8	68	101.1	150
K.V @ 100°C cSt	5.4	6.8	8.7	10.9	14.9
Viscosity Index	100	100	100	100	100
Flash Point °C	225	220	244	268	270

Availability

Cages Ultracomp H2000 compressor oils are available in bulk, 1000 litre IBC's, 205 litre barrels, 25 litre drums 5 litre and 1 litre plastic bottles.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health and Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Cages ltd is one of continual improvement; we therefore reserve the right to change specifications without notice.